

Holding Ground

by Travis Nech

Free edition — metrofoundationrepair.com

HOLDING GROUND

A Texas Homeowner's Year-Round Guide to Soil Moisture, Plumbing Leaks, Tree Roots, and Keeping Your Foundation Where It Belongs

Travis Nech

© 2026 Travis Nech. All rights reserved.

ISBN pending KDP assignment

No part of this book may be reproduced or transmitted in any form or by any means without written permission from the author, except for brief quotations used in reviews.

This book is educational information based on 50 years of hands-on field experience in brick, masonry, and foundation work across Texas. It is not a substitute for an on-site evaluation of your specific house. Conditions vary from lot to lot and house to house. Where this book suggests getting an independent opinion, hiring a structural engineer or a licensed plumber for work in their trades is money well spent.

Contents

- Introduction: A House You Can Keep Steady
- Chapter 1: The Ground Under Your House Never Sleeps
- Chapter 2: Texas Clay: Why It Swells, Shrinks, and Moves Your House
- Chapter 3: Reading Your House: Floors, Doors, and Small Signs That Matter
- Chapter 4: Water Is the Whole Game: Rain, Drought, and Soil Moisture
- Chapter 5: Watering Your Foundation the Right Way
- Chapter 6: Trees, Roots, and the Thirst Around Your House
- Chapter 7: Plumbing Leaks Under the Slab: The Hidden Foundation Killer
- Chapter 8: Drainage That Protects Without Drying You Out
- Chapter 9: Inside the Repair: Pressed Concrete Piles to Refusal, Explained Simply

- Chapter 10: After the Repair: The First Year and Every Year After
 - Chapter 11: Buying, Selling, and Living With a Repaired Foundation
 - Chapter 12: Your Year-Round Foundation Care Calendar
 - Conclusion: Holding Ground for the Long Haul
 - Resources & Next Steps
 - About the Author
-

Introduction: A House You Can Keep Steady

Most Texas homeowners do not think about their foundation until a door stops latching, a crack opens over a window, or a floor starts to feel different underfoot. By then the worry arrives all at once, usually along with a sales pitch, a big number, and a lot of words that do not quite explain what is happening under the house.

This book was written to slow that moment down and put you back in charge of it.

A foundation is not a mystery, and it is not magic. Your house sits on ground, and in most of Texas that ground is clay that swells when it gets wet and shrinks when it dries. The ground moves a little with every wet spring and every long, hot summer. Whether that movement stays small and harmless, or grows into sticking doors, cracked walls, and a slab that needs repair, depends mostly on one thing you can influence every week of the year: how even the moisture stays in the soil around and under your house.

That is the heart of this book. You will learn how Texas clay behaves, how to read the small signs your house gives you, and how to tell a seasonal wiggle from a change that keeps getting worse. You will learn how to water a foundation sensibly, what trees and shrubs really do to the soil, and why a plumbing leak under a slab can undo in months what drought takes years to do. You will learn how drainage protects a house without drying it out, and, if repair day ever comes, how pressed concrete piles driven to refusal work, in plain language, so you can judge what you are being told.

Just as important, you will learn what to do after a repair. A repaired foundation is not a house you stop caring for. It is a house whose weak ground has been bypassed and set on ground that proved it can hold the load, and it stays that way best when the moisture care in this book becomes a habit.

Nothing in these pages requires special tools or a technical background. A garden hose used with thought, a notebook by

the kitchen drawer, a walk around the house after a hard rain, and the habit of fixing a leak fast will carry you most of the way. Where a job belongs to someone else, this book says so plainly. Leak detection and plumbing repair belong to a licensed plumber. Questions about whether a specific house is safe belong to a structural engineer you hire for an independent opinion. Foundation evaluation and repair belong to a contractor who will show you measurements, explain refusal, and put the paperwork in your hands.

I have spent 50 years in brick, masonry, and foundation work across Texas. I have watched the same street produce one house that never moves and another that needs help, and the difference is very often not how the houses were built. It is how the water was handled, year after year, by the people who lived in them.

Your house can be the steady one. This book shows you how, season by season.

Chapter 1: The Ground Under Your House Never Sleeps

Most people think of the ground under their house like a parking lot. Solid. Still. Done. You build on it, and it just sits there holding everything up.

Texas ground does not work that way.

The soil under your home is changing all the time, even when you cannot see it, even in a dry week, even in the middle of the night. It takes on water and gives water up. It swells a little and shrinks a little. It warms and cools. Roots grow through it, water moves through it, and the weight of your house presses down on it day after day, year after year. Your foundation is not resting on something frozen. It is resting on something alive with moisture change.

That one idea explains more about Texas foundations than almost anything else. A door that worked fine in April sticks in August. A small crack looks wider in a drought and tighter after a wet spring. A floor develops a gentle slope you notice when a marble rolls. None of that means your house was built badly. It means your house is sitting on Texas soil, and Texas soil moves.

A House Sits on the Ground, Not Apart From It

We talk about houses as if they are separate from the land.

We say "the house" and "the yard" as if they are two different worlds. In real life, they are one system.

Rain that falls on your roof runs off somewhere. Rain that falls on your yard soaks in somewhere. Water from a flower bed, a sprinkler, or a slow plumbing leak does not stay politely where you put it. It moves through the soil, often sideways, and can reach the soil under your slab or footings. Heat does quiet work from the other direction. A long stretch of hot, dry weather pulls moisture out of exposed soil first, then out of soil closer to the house.

Your foundation sits in the middle of that exchange. Think of it as a boat, not an anchor. A boat floats, and even a well-built boat rises and falls a little with the water. A concrete slab is stiff and strong, but it still rides on the soil below it. When that soil gains moisture and expands, it can lift. When it loses moisture and shrinks, it can drop and leave less support underneath. The house goes along for the ride.

That does not mean every home is in trouble. Most movement is small, slow, and part of normal life in this state. Houses are built expecting some of it. Builders compact soil, pour thickened edges called grade beams around the perimeter of a slab, and design the slab to span small changes in support. Those steps help. They do not make the soil stop changing. After 50 years of hands-on field experience looking at houses across Texas, I can tell you plainly: the best-built house in the neighborhood still lives on the same clay as the house next door. Good construction gives you more tolerance for movement. It does not give you immunity from it.

Why Foundations Move in Well-Built Houses

Homeowners often ask the same question, and it is a fair one: "If my house was built right, why is it moving at all?"

There are several honest answers, and usually more than one is true at the same time.

First, the weather is bigger than any one house. Texas can swing from soaking spring rains to a summer with almost no rain, sometimes in the same year. Soil moisture follows that swing, with a delay. Deep soil changes more slowly than surface soil, which is why movement often lags behind the weather by weeks or months. The drought you worry about in July may show up in your doors in September.

Second, the ground under a house is not all the same. One corner may sit over soil that holds more clay, while another drains faster. One side may get full afternoon sun and dry out hard, while the other stays shaded and damp. Additions, porches, and driveways change how water moves. Uniform

soil would move more uniformly. Real lots are not uniform.

Third, life around the house changes over time. A tree that was a skinny sapling when the house was built is a large, thirsty tree twenty years later. Landscaping goes in and comes out. Sprinkler habits change when owners change. The house did not change, but everything acting on the soil around it did.

Fourth, small water sources matter more than most people expect. A slow leak that never makes a puddle can still change the moisture under a slab over time. A gutter that dumps roof water in one spot feeds one area of soil far more than the rest. An air-conditioning drain line that drips in the same place all summer keeps one patch wet while everything around it dries. Foundations respond to patterns, not just to big events. None of these causes requires anyone to have done something wrong.

What "Foundation Trouble" Actually Means

The phrase "foundation trouble" gets used for almost everything, and that loose language scares people without helping them.

A hairline crack in drywall is not the same thing as a foundation that has lost support and dropped several inches. A door that rubs in late summer is not the same thing as a door that has steadily gotten worse for three years and now will not latch at all. A tile crack is not a verdict. A brick crack is not a verdict either. Each one is a clue, and clues have to be read together, over time, in context.

It helps to separate three ideas that often get tangled together.

The first is normal settling. When people say a house is "settling," they usually mean small, early adjustments after construction as the weight of the house compresses the soil and the materials find their place. Some of that is expected, it tends to slow down, and by itself it is not a reason for alarm. The word "settling" is not a diagnosis. It is a general description, and it should never be used to wave away changes that keep getting worse.

The second is seasonal movement. This is the up-and-down rhythm many Texas houses show with the wet and dry seasons. Doors and cracks change a little, then change back, at least in part. The question is how much there is, whether it returns to roughly the same place each year, and whether it interferes with how you live in the house. A house can have seasonal movement for decades and never need repair, as long as it stays modest and cycles instead of marching in one

direction.

The third is progressive movement, and this deserves prompt attention. Progressive means the change keeps going the same way and does not recover when the season changes. A crack keeps widening. A slope keeps increasing. Often there is a cause feeding it — a leak that never stops, drainage that keeps sending water to one place, or drying that keeps pulling support away from one side. Progressive movement is what "foundation trouble" should be reserved for.

Learning to tell these apart is the heart of this book. You need a clear eye, a few simple habits, and a sense of when watching is enough and when it is time to bring in help.

Why Texas Is a Hard Place for Foundations

Texas is not the only state with moving soil, but it earns its reputation honestly.

Much of the state, and especially the broad band that runs through the Dallas-Fort Worth area and down through Central Texas, sits on soils with a high clay content. Clay is the main character in the next chapter, so for now just hold this picture: clay soil changes size when its moisture changes, more than sandy or rocky soil does. Where clay is deep and widespread, foundation movement is not an exception. It is a condition of the place.

On top of that, our weather gives clay plenty to react to. Long, hot summers bake moisture out of the ground. Droughts can run for months. Then heavy rains can arrive all at once, soaking dry, cracked soil very unevenly. A hard rain on very dry ground does not always soak in evenly — some runs off, some rushes into cracks and goes deep in one spot. The result is soil moisture that is different from place to place under the same house, and different support is what makes a slab tilt, a footing drop, or a wall crack in a pattern.

Texas homes also use foundation types that interact directly with this soil. Many houses sit on slab-on-grade foundations, where the floor you walk on is the foundation itself. Others, especially older homes, sit on pier-and-beam foundations, where wood framing rests on piers above a crawl space. Both can perform well for a long time. Both respond to what the soil does underneath them.

None of this is a reason to worry every day. It is a reason to pay attention in a steady, unhurried way. The homeowners who do best here are not the ones who panic at the first crack or the ones who ignore everything. They are the ones who learn how their house behaves through the seasons, keep moisture around the house as even as they reasonably can, fix

water problems promptly, and keep simple notes.

In the chapters that follow, we will take this one piece at a time: the clay itself, the signs your house gives you, the role of water, what trees do, what a real evaluation looks like, and how repair works when repair is truly needed. For now, keep this picture in mind. The ground under your house never sleeps. Once you accept that, you start reading your house as it deserves to be read — as a strong, useful home sitting on living Texas ground, asking you to work with that ground instead of pretending it is not there.

Chapter 2: Texas Clay: Why It Swells, Shrinks, and Moves Your House

If Chapter 1 had a main character under the ground, this chapter gives that character a name: clay.

Not all soil is clay, and not all clay behaves the same way. But across much of Texas, clay is the reason foundations move the way they do. Understanding clay in plain terms will save you a lot of confusion, because once you see how it takes on water and lets water go, the behavior of your house stops looking random.

Start with what soil actually is. Soil is a mix of small pieces of rock and mineral, in different sizes, with air and water in the spaces between them. Sand is made of larger grains. Water runs through sand quickly, and sand does not change size much when it gets wet or dry. Silt is finer. Clay is the finest of all — so fine that the particles are far too small to see, and they are flat, more like tiny plates than round grains.

That shape matters. Flat, tiny particles hold onto water in a way sand does not. Water does not just pass through clay and leave. It gets taken in between the particles, and the clay changes as a result. That is the whole story in one sentence: clay absorbs water, swells, gives water up, and shrinks.

The Wet Swell and the Dry Shrink

Think of a dry kitchen sponge in a drawer. It is small, stiff, and light. Put it under a faucet and it grows. It softens, thickens, and takes up more space. Let it dry out on the counter for days and it shrinks back down and gets stiff again.

Expansive clay — the kind that causes the most foundation movement in Texas — works in a similar direction, only much more slowly and with the weight of a house on top of it. When expansive clay gets wet, it swells and pushes. That push is

called heave when it lifts a foundation or a floor. Clay does not need a flood to do this. A steady source of moisture, week after week, can raise the moisture in clay under one part of a house and lift that part a little.

When expansive clay dries, it shrinks and pulls away. Soil pressed against the bottom of a slab or footing can lose volume, crack at the surface, and leave a gap where support used to be. The foundation there has less to rest on, so it can settle or drop a little. The surface cracks you see in a dry yard in August are a visible hint of it. Those cracks are not damage by themselves. They are a sign the soil is dry and has contracted — the same process that, under a house, can reduce support at the edges.

Now run that cycle over and over. Wet spring, swelling. Hot summer, shrinking. Year after year. That repeated cycle is the engine of most Texas foundation movement. One cycle rarely breaks a house. Many cycles, especially uneven ones, work on a house slowly, and in the places where movement is greatest.

The key word is uneven. If all the soil under a house swelled and shrank the same amount at the same time, the whole house would rise and fall like an elevator, and you might never notice. Damage comes from differential movement — one part moving more than another. One corner lifts while another stays put. One edge drops while the middle holds. The house, built level and square, is now asked to bend a little, and houses are not good at bending. Drywall, brick, tile, and door frames show the strain first because they are stiff.

Different Ground Across DFW and Central Texas

Texas is large, and its soils change from place to place, sometimes within the same neighborhood and sometimes within the same lot. You do not need a soil map of your street to use this book well, but a few general patterns help.

In the Dallas-Fort Worth area, many neighborhoods sit on dark clay soils well known for swelling and shrinking. Areas east and northeast of Dallas often have deep clay that stays active through a wide range of moisture. Around Fort Worth there is clay as well, along with places where limestone and rock are closer to the surface — shallower soil over rock in one spot, deeper clay in a low spot nearby. That mix can be tricky: rock does not shrink, clay does, so a house partly over each can get different support on different sides.

Farther south through Central Texas, around Waco, Temple, and down toward Austin and San Antonio, you will find broad areas of expansive clay, clay over limestone, and thinner,

rockier soil in hillier ground. A low, flat lot may hold deep clay and water longer. A sloping, rocky lot may drain quickly and still have pockets of clay that move. The lesson is not to memorize a map. What matters most is the soil on your lot and how water behaves there through the year.

Even inside one city, builders meet very different ground on lots a few streets apart. One subdivision may have been built on ground cut down to firmer material, another on ground that was filled to bring it up to grade. Fill — soil brought in and compacted to level a lot — can behave differently from undisturbed soil, especially if it holds a lot of clay. Two identical houses built the same year can behave differently simply because the ground work under them was different. Do not judge your house only by what happened to a neighbor's house.

If you ever need to know your soil in a formal way, that is work for testing and for a licensed professional who studies soil and structures. For day-to-day care, your job is simpler: notice where water collects, where the ground dries and cracks first, and where your house shows seasonal changes.

How Deep the Movement Goes

Homeowners often picture the moving soil as just the top few inches — the part they can dig with a garden trowel. The active zone goes deeper than that.

The active zone is the depth of soil where moisture changes enough, season to season, to cause swelling and shrinking. In Texas that zone commonly reaches several feet down, and in some places and in severe droughts, the drying influence can reach deeper still. The exact depth varies with the soil, the climate, trees, and how the surface is covered. As a plain-language picture, think in feet, not inches.

This depth explains a timing puzzle. Surface soil responds to rain in hours or days. Soil three or four feet down responds in weeks. Deeper soil may respond over a season. So your yard can look recovered two weeks after a drought-breaking rain while the soil under the middle of your slab is still dry, and your doors have not changed back. It also explains why soaking the yard for one weekend rarely changes what is happening under a house. Moisture management is about steady, moderate, even moisture over time, not flooding one weekend and forgetting it the next. Later chapters will take up that care in detail.

Cover matters, too. Soil under the middle of a slab is protected from sun and wind by the house itself. It dries and wets slowly, mostly from moisture moving sideways from the edges. Soil at the perimeter is exposed to everything: sun,

wind, rain, sprinklers, and tree roots. That is why changes are usually greatest near the outside of the house and smaller toward the center.

Why the Edges Move More Than the Middle

Stand in the middle of your house and walk to an outside wall. In foundation terms, you just walked from the most sheltered soil to the most exposed soil.

The middle of a slab sits over soil that keeps a more stable moisture level through the year. It is covered and far from the direct effects of weather. It tends to move the least, and the slowest.

The edges are the opposite. Soil just outside and just under the perimeter gets rained on, baked, watered, and reached by roots first. Its moisture swings the most, so it swells and shrinks the most. The grade beam around the edge follows that soil as it moves. As a result, many Texas houses show edges lifting in wet periods or dropping in dry periods while the middle stays comparatively still — or long-term moisture under the middle keeps it higher while the edges dry and drop around it. Either pattern puts a gentle dome or dish shape into a floor that was poured flat, and you feel it as slope and notice it in doors near outside walls.

Hypothetical example: Imagine two identical houses on the same street in late August, after ten weeks with almost no rain. At the first house, the owner has watered the foundation area lightly and evenly all summer. At the second, no one has watered, the sunny sides are baked, and the soil has pulled away from the slab in a visible gap. Both sit on expansive clay. The first may show almost no new signs that month. The second may show sticking doors on the sunny side and a crack at a corner. The difference was not the clay. It was how unevenly the clay was allowed to dry.

That principle is hopeful: you cannot change that your soil is clay, if it is. You can change how uneven its moisture gets, how quickly water problems are fixed, and how early you notice a pattern. Those are homeowner-sized jobs, and they make a genuine difference.

Keep the sponge in mind as you read on. Every sign in the next chapter, every leak, root, and downspout in the chapters after that, matters because of what it does to water in clay. Wet, it swells and pushes. Dry, it shrinks and lets go. Your house is riding on that slow, powerful cycle — and knowing the cycle is the first step to holding your ground.

Chapter 3: Reading Your House:

Floors, Doors, and Small Signs That Matter

Your house talks in small changes: a door that starts to rub, a crack that was not there last spring, a floor that feels different under your feet in one room. Learning to read those signs calmly is one of the most useful skills a Texas homeowner can have.

Reading a house does not mean worrying about it. It means noticing, writing it down, and watching how it behaves over time. A single sign rarely tells you much. A pattern of signs, in the same area, moving in the same direction over months, tells you a great deal.

Doors That Stick, Swing, or Will Not Latch

Doors are some of the best early reporters in a house, because a door and its frame start out square and close-fitting. Even a small change shows up quickly.

A door that sticks at the top corner, rubs on one side, or needs a lift to latch is telling you the frame is no longer perfectly square. That can happen when the foundation under that part of the house lifts or drops a little. Look at the gap around a closed door. A healthy door has a fairly even gap. If the gap is wide at one top corner and tight at the other, note it.

Also notice which doors are affected. One interior door near an outside wall that changes with the seasons is a common Texas story. Several doors on the same side of the house, changing at the same time and getting worse, is a stronger signal. An exterior door that will not lock properly deserves quicker attention than a closet door that rubs a little each August, both for security and because exterior doors sit on the perimeter, where movement is greatest.

Do not rush to fix the door itself before you understand the pattern. Planing a door in the middle of a seasonal swing can leave you with a door that fits poorly when the house moves back. If you do adjust a door, note what you changed and when.

Windows deserve the same attention. A window that becomes hard to open, or that shows a small crack at one corner of its frame, is reporting the same kind of strain.

How a Floor Feels Under Your Feet

Floors tell their story more quietly. Most people first notice a slope not with a tool, but with their body: a room that feels

like it tilts toward one wall, a table that needs a shim under one leg where it never needed one before.

Trust that feeling enough to check it, but do not trust it alone. Simple checks help. A marble on a hard floor will roll toward a low area — or sit still, which is also useful information. A long level laid on the floor in several directions can show whether a slope is real and which way it runs. Walking the house barefoot, room by room, once or twice a year and noting where the floor feels high, low, bouncy, or sloped builds a familiarity no single visit can match.

In a pier-and-beam house, pay attention to bounce as well as slope. Floors there can feel springy when framing or piers need attention, and a crawl space gives you, or a professional you hire, a place to look directly at the structure. In a slab house, the floor is the foundation, so slope in the floor is slope in the foundation itself.

What matters is not whether your floor is perfectly level. Few floors stay perfect for decades on Texas clay. What matters is change: a slope that is new, growing, or lined up with door problems and cracks in the same area.

Cracks Are Clues, Not Verdicts

Nothing worries a homeowner faster than a crack, and nothing is misread more often.

Start with a calming fact: cracks have many causes, and most small cracks are not a foundation emergency. Drywall joints crack from small seasonal movement and from the normal drying of building materials. Brick can develop small step cracks — cracks that follow the mortar joints in a stair-step pattern — as a wall responds to movement at its base. Concrete can crack from curing when it is new.

How do you read a crack usefully? Look at where it is, how wide it is, what direction it runs, and whether it is changing.

Location matters. Cracks at the corners of doors and windows are common stress points and are often the first place seasonal strain shows. Cracks in several rooms that all point to one corner or side of the house carry more weight.

Width matters, in a rough way. Hairline cracks — the kind you can barely get a fingernail into — are usually watched, not acted on. Wider cracks, and cracks where one side sits higher than the other, deserve closer attention and, if new or growing, a professional evaluation.

Pattern matters. A single drywall crack is a weaker clue than a set of cracks that together describe one area moving. A

sticking door, a diagonal crack above that door, and a step crack in the brick outside the same room are three clues telling one story.

Change matters most. A crack that has looked the same for five years is part of your house's normal character. A crack that is longer, wider, or joined by new cracks since last season is active. You cannot judge change from memory alone, which is why the log below is so valuable. Place a small pencil mark at the end of a crack, with the date, in an inconspicuous spot. If the crack grows past your mark, you will know.

Hypothetical example: A homeowner finds a hairline crack above a living room window in September, photographs it with a coin beside it for scale, and writes down the date. In January it looks the same. The following September it looks the same again. That pattern points toward seasonal movement to keep watching. If it had widened at each check and a nearby door had begun to stick, calling for an evaluation would have been right.

Seasonal Signs and Progressive Signs

Seasonal signs come and go, at least partly, with moisture and temperature. They tend to be worst in late summer after long drying, and they ease when conditions reverse. They repeat in the same places each year without steadily getting worse. Seasonal signs call for steady moisture care and continued watching.

Progressive signs do not reset. They advance a little, hold, then advance again, or advance steadily. They often gather company — a crack joined by a door problem, joined by a slope. Progressive signs call for action: find the cause, and get an evaluation.

You often cannot tell which kind you have from one season alone. That is the reason for the log. Two or three dated observations across different seasons usually make the pattern clear, and make any later evaluation far more useful.

Keeping a Simple Home Log

Your log does not need to be fancy. A notebook in a kitchen drawer, or a note on your phone, is enough if you use it consistently. The best log is the one you will actually keep.

Write down the date, the room, what you noticed, and anything about recent weather or water that might matter. "August 12 — back bedroom door sticking at top, needs lift to latch. No rain in six weeks. Soil pulled away from slab on south side." That entry is worth more than a worried guess a

year later. Add a photo when you can, from the same spot each time, with something of known size for scale. Note repairs and changes too: a plumbing repair, a new sprinkler schedule, a large tree removed. Those events often explain later changes.

Do a walk-through twice a year — once in wet spring and once in dry late summer. Open and close the doors. Look at the known cracks. Walk the floors. Look at the brick and slab edge outside. Write down what is the same as well as what is different. "No change" is valuable information.

When to Watch, When to Call, and When to Get an Independent Opinion

Watch when signs are small, stable, and seasonal. Watching is not ignoring. It means logging, photographing, caring for moisture around the house, and checking again on schedule.

Call for a foundation evaluation when signs are progressive, when several signs cluster in one area, when a crack is wide or offset, when doors or windows stop working and stay that way, when you see a new slope, or when you suspect a plumbing leak — a water bill that rises without explanation, or a spot that stays wet. An evaluation should include measurements of floor levels, a walk inside and outside, and a clear explanation of what was found and what is recommended, including doing nothing and monitoring, if that is reasonable. If repair is recommended, the method this book covers is pressed concrete piles, driven to firm support to lift and hold the affected area. Get the recommendation in writing, with a drawing of where work is proposed. Costs vary widely, so treat any early number as a rough ballpark until it is based on measurements of your home.

One more step is available: hiring a structural engineer for an independent opinion. An engineer hired by you, who is not selling repair work, can evaluate your foundation, explain likely causes, and say in a written report whether repair is needed or whether monitoring is right. That report is especially valuable before a large repair decision, when companies disagree, or when you are buying or selling. There is a cost, and it varies widely, but for a major decision it is often money well spent. My authority in these pages is 50 years of hands-on field experience. On a big call, an independent engineer's report is a sound way to protect yourself.

Read signs early, read them together, write them down, and you will have time to act wisely instead of reacting in a hurry. That is holding ground.

Chapter 4: Water Is the Whole Game: Rain, Drought, and Soil Moisture

If you remember only one idea from this book, let it be this one: your foundation does not want a lot of water, and it does not want no water. It wants the same water, all the way around, all year long.

Texas weather works against you: weeks with no rain, then a storm that drops inches in an afternoon, then a summer that bakes the yard hard enough to crack.

Most homeowners think of foundation trouble as a house problem. After 50 years of hands-on field experience looking at houses across Texas, I can tell you it is almost always a soil problem first. The concrete is strong. What changes is the ground holding it up. When that ground swells in one place and shrinks in another, the foundation has to follow. That uneven movement is what shows up inside as sticking doors, cracks in drywall, gaps at trim, and floors that do not feel quite level.

The soil under a Texas house is not still

A lot of Texas sits on clay-rich soil. Clay behaves very differently from sand or rock. When clay gets wet, it absorbs water and expands. When it dries, it loses water and shrinks, sometimes by a surprising amount. It does not do this evenly, and it does not do it quickly in the deep layers. The top few inches can change in a day. The soil two or three feet down, right where it matters most, changes over weeks and seasons.

Think of the soil like a very large, very slow sponge. A light rain may never reach deep. A long, steady rain soaks in gradually. A hard downpour mostly runs off dry, hard ground. During drought, that sponge slowly gives up moisture to air, grass, and tree roots, and keeps shrinking long after the last rain.

That word — uneven — is the heart of it. If the entire yard swelled a little in winter and shrank a little in summer, together, the house would rise and settle as one piece and you might never notice. What actually happens is that one side gets more water than the other. The south and west sides bake in afternoon sun and dry faster. The north side stays shaded and holds moisture longer. One corner sits under a roof drip line and gets flooded every storm, while another corner sits under a wide eave and almost never gets rain. The soil moves differently in each place, and the foundation gets pulled in different directions at the same time.

What a downpour really does

A heavy Texas rain feels like it should solve a dry-soil problem. Sometimes it helps a little. Often it does less than you think, and sometimes it creates a new problem on top of the old one.

First, water that arrives fast tends to leave fast. On dry, compacted clay, the surface seals up quickly. Much of a downpour sheets off the yard, runs down the street, or stands in low spots instead of soaking down where the foundation needs steady moisture. You can get two inches of rain in an hour and still have dry soil a foot down at the edge of the slab two days later.

Second, a downpour is rarely even. Roof water is the big reason. A roof collects rain from a large area and dumps it in a few concentrated places — at valley ends, at downspout outlets, at any place where a gutter overflows. That one spot can receive many times more water than the open yard a few feet away. The soil there swells while the soil ten feet away stays dry. That is exactly the uneven pattern you are trying to avoid.

Third, standing water changes the soil right against the house. If water puddles next to the foundation and sits for hours or days, the clay in that narrow band gets saturated. It softens and swells. Then, when the sun comes back, that same band dries from the top down and shrinks again. Repeated soaking and drying in the same narrow strip, right at the edge, is hard on a foundation over the years.

None of this means rain is bad. Rain is essential. A slow, soaking rain over a full day is some of the best medicine Texas soil gets. It is the violent pattern — bone dry, then flooded, then bone dry again — that wears a house down.

What a long drought really does

Drought does its work quietly. Week after week, the soil gives up moisture. Grass thins. The yard pulls away from sidewalks and from the foundation itself. Cracks open in the ground. Those cracks matter for two reasons.

The first is shrinkage. As clay dries, it contracts, and it can lose support under the edge of a foundation. The middle of the house, protected from sun and wind, often stays more moist than the perimeter. So during a long drought the edges tend to drop while the center holds closer to where it started. Inside, that can look like doors on exterior walls binding, cracks opening around windows, and separation at the corners of rooms.

The second reason is what happens when rain finally returns. A crack in dry clay is an open channel. The next rain does not just wet the surface evenly. It pours straight down those cracks, fast and deep in some spots and not at all in others. That is another recipe for uneven swelling.

Drought also changes everything else around the house. Trees and large shrubs work harder to find water, and their roots draw more moisture from the yard and, in some cases, from near the foundation. Sprinkler systems that were adequate in May fall behind in August. It all adds up in the same direction: the perimeter soil gets drier than the soil under the center of the house, and the gap gets wider the longer the dry spell lasts.

Puddling edges and drying edges at the same house

The same house can have a too-wet problem on one side and a too-dry problem on another, at the same time.

Hypothetical example: Picture a home with a downspout that dumps roof water into a flower bed on the east side, with nowhere for that water to go. That bed stays soggy after every rain, and the soil there stays swollen. On the west side, there is no downspout, just a wide eave, full afternoon sun, and a big shrub pulling moisture out of the ground. That side dries and shrinks all summer. The foundation is lifted on one side and let down on the other, not because anything is broken, but because water is delivered very unevenly.

That is why the first thing to look at with any foundation concern is not the crack inside. It is the water outside. Walk the whole perimeter after a rain and again after a dry week. Where does water stand? Where does it run? Where is the soil pulled away from the slab? Where is it tight and damp? The pattern tells you a story a single crack never can.

Drying edges are easier to miss because nothing looks wrong at first. The soil just slowly recedes. You might notice a gap opening between the soil and the slab, or between the soil and a sidewalk. That gap is information. It tells you the clay has shrunk, and that the next heavy rain will pour into that opening if it is left alone. Keeping that edge from drying to that point is far better than trying to catch up after it happens. The next chapter is devoted to exactly that job.

Why sudden soaking after drought is hard on a house

It feels kind to a dry yard to flood it. After weeks of watching the ground crack, many homeowners put a hose at the

foundation and let it run for hours, or welcome a huge storm as the cure. I understand the instinct. The soil, however, does not rebound evenly from a sudden soaking, and that is where the trouble comes in.

Dry clay swells as it takes water back, but it swells first where the water arrives first — at the surface, at crack openings, at the one spot where the hose sat. Deeper soil and soil a few feet away may still be dry and shrunken. For a time, you can actually increase the unevenness you were trying to fix. The edge lifts in spots while other sections lag behind. A house does not need that kind of quick, patchy lift.

The lesson is not to withhold water. The lesson is to add water the way soil can use it: slowly, evenly, and over time. Little and often beats a flood after a drought, every time. Foundations like boring. They like the same routine, week after week, adjusted gently as the seasons change. They do not like rescue missions.

If you take a single habit from this chapter, let it be watching. Check the soil at the edge of your foundation regularly, in the same few spots, so you learn what normal looks like at your house. Push a long screwdriver or a soil probe into the ground near the slab. Is it damp a few inches down, or powder dry? Does it look the same on the shaded side as on the sunny side? You are not looking for a perfect number. You are looking for a big difference from one side to the other, because that difference is what moves houses.

In the next chapter we will get practical: how to water a foundation on purpose, where to place a soaker hose, how mulch and beds and sprinkler systems help or hurt, and how to do it sensibly even when your city asks everyone to use less water. The goal never changes. Even moisture, all the way around, all year long.

Chapter 5: Watering Your Foundation the Right Way

Watering a foundation sounds odd the first time you hear it. You water grass. You water flowers. Why would you water concrete?

You are not watering the concrete. You are watering the soil next to it, on purpose, to keep that soil from shrinking away during dry weather. It is one of the simplest and least expensive things a Texas homeowner can do, and when it is done steadily and evenly, it prevents a great deal of the movement described in the last chapter. When it is done in a rush, in one spot, or only after the ground has already cracked wide open, it helps much less — and can even add to

the unevenness you are trying to avoid.

This chapter is not a rigid prescription. Every yard is different. Soil, shade, slope, trees, beds, and city rules all change the picture. What follows are principles you can adjust to your house, thinking by season rather than following the same timer setting all year. If you are ever unsure about a serious movement problem, that is a good time to get an in-person opinion, and for structural questions, to consult a structural engineer. For everyday moisture care, though, most homeowners can do this work themselves with a hose, a timer, and a regular walk around the house.

Soaker hoses: slow is the whole point

A soaker hose is a hose that weeps water along its length instead of spraying it. That slow weep is exactly what clay soil needs. A sprinkler throws water into the air, loses some to wind and evaporation, and delivers it faster than dry clay can absorb it, so much of it runs off. A soaker hose laid on the ground delivers water quietly, at ground level, where it can soak down over hours.

Use enough hose to run along the sides of the house that dry out, not just the one corner that worries you most. Remember the goal from Chapter 4: even moisture all the way around. Watering one side faithfully while ignoring the others can create the very difference you are trying to prevent. If a side stays naturally damp and shaded all summer, it may need little or no added water while the sunny sides need regular help. Even does not always mean identical. It means the soil ends up in a similar condition on each side.

Keep the pressure low. A soaker hose turned on full blast will jet from the holes nearest the faucet and barely weep at the far end. A gentle flow, sometimes with a pressure reducer or with the faucet opened only partway, gives a more even result along the full length. Check it after you first set it up. Walk the line and look for dry sections and for spots where water is pooling. Adjust, move the hose a little, and check again. The first setup takes a little patience. After that, the routine is easy.

Distance from the slab, and why it matters

Place the soaker hose a short distance out from the foundation, not pressed tight against it — commonly about a foot to a foot and a half out, as a general starting point you can adjust for your beds and walkways. There are two reasons for that gap.

First, you do not want to deliver water directly into any crack or joint right at the edge, or to keep the narrow strip touching

the house saturated while the soil farther out stays dry. Water placed a little way out soaks down and spreads inward and outward, moistening a wider band of soil more gradually.

Timing and frequency: think by season, not by habit

The most common mistake is setting a schedule in June and never changing it, or watering only when the yard already looks desperate. Soil moisture changes slowly, so your watering should change slowly too, ahead of the soil rather than behind it.

In spring, rain often does much of the work. Your job is mostly to watch. Check the soil at the slab edge after dry weeks. If the ground is still damp a few inches down and there is no gap at the edge, you may need little added water. If a warm, windy stretch dries the sunny sides early, start light, occasional soaking there before cracks appear.

In summer, demand is at its highest. Sun, heat, and wind pull moisture out daily, and trees and shrubs pull it out from below. This is when a regular, modest routine matters most — shorter, more frequent soaking is generally kinder to clay than one very long soak once in a while. Early morning is usually best: less evaporation than midday. How long and how often varies widely with soil, shade, and local conditions, so use the soil check, not the calendar alone. Aim for damp soil a few inches down, not mud on the surface.

In fall, do not quit all at once because afternoons feel cooler. Taper gradually as rains return and the soil check shows moisture holding on its own.

In winter, most Texas foundations need far less added water, and in a wet winter none. But a long, dry, windy winter can still dry the south and west perimeter. An occasional check on a mild day is enough for most homes; if soil is dry and pulled away, a light soaking when no freeze is expected beats ignoring it until spring.

Mulch and flower beds: helpers with conditions

Mulch is a genuine help. A layer of mulch over beds and over the soil near the foundation shades the ground, slows evaporation, softens the impact of hard rain, and keeps soil temperature more even. Beds that are mulched hold moisture noticeably longer than bare soil in August. Keep the mulch a few inches deep, refresh it as it thins and breaks down, and keep it from piling up against siding or covering the edge where you need to inspect the foundation.

Flower beds themselves can help or hurt, depending on how they are built and watered. A bed that is watered regularly with the rest of the foundation routine can keep the soil at that side in good shape. A bed that is raised high against the house, holds water like a bowl, or is watered heavily while the rest of that side gets nothing creates uneven moisture. Beds that slope so water collects at the house are a drainage problem first and a planting problem second. Fix the slope and the downspout delivery before you blame the plants.

Sprinkler systems: real help, real harm

An in-ground sprinkler system can be a foundation's friend, because it waters on a schedule whether you remember or not, and it covers the yard evenly when it is working well. It can also quietly cause harm in ways homeowners do not notice for years.

Harm looks like this: a head that has sunk or turned and now sprays the side of the house or a sidewalk instead of the soil; a leaking line or valve that keeps one small area soggy while the rest dries; a zone that waters a flower bed heavily and the adjacent lawn barely at all; and, very commonly, a dry gap right at the slab. That gap happens because eaves shelter the strip next to the house from rain, heads are set out in the yard aiming outward, and shrubs block the spray. The lawn can look green while the soil at the foundation is the driest on the lot.

Walk your system while it runs a few times a year, and check the slab edge after a cycle.

Checking for dry gaps at the slab edge

Make this a habit: every week or two in dry weather, walk the foundation slowly. Look at the line where soil meets concrete. A small hairline shadow is normal. A gap you can slide fingers into, soil that has dropped and cracked away, or exposed footing in extreme cases is a sign the perimeter has dried and shrunk.

Hypothetical example: A homeowner waters the lawn faithfully all summer and assumes the foundation is fine because the grass is green. On a walk in August she finds the west side soil pulled an inch away from the slab, dry several inches down, while the shaded east side is still damp and tight. Nothing inside the house has cracked yet. She has caught the difference early, when steady, gentle watering of the dry side over the following weeks — not a single flood — can bring the moisture back toward even without a repair bill.

Water restrictions and being sensible

Many Texas cities limit outdoor watering in drought, sometimes to certain days, sometimes by hand or soaker use, sometimes with broader limits. Always follow your local rules. They are not optional, and this book is not suggesting otherwise. Within those rules, foundation care is usually still possible, because soaker hoses and hand watering use water slowly and with very little waste compared with spraying on a windy afternoon.

Be sensible. Water early, keep the flow low, avoid runoff into the street, fix leaks, and do not water when rain has done the job. If restrictions bar added watering, focus on what you still control: mulch, drainage that spreads rain evenly, and gentle attention when restrictions ease.

Costs for this care are generally modest compared with repair — soaker hoses, a timer, and mulch are ordinary hardware-store purchases — but prices and water rates vary widely by town and yard size, so plan for your own situation. If movement does progress to repair, in our work that repair means pressed concrete piles, and its cost also varies widely. Prevention will almost always be the less expensive path.

Start where you are. Lay a soaker along the driest side, check the soil, learn how your ground responds, then extend the routine around the house. Steady and even, adjusted by season, verified by looking — that is watering the right way.

Chapter 6: Trees, Roots, and the Thirst Around Your House

Every Texas homeowner who loves a big shade tree eventually asks the same question: is that tree hurting my foundation?

The honest answer is sometimes, and it depends. A tree is not an enemy. Shade cools the soil and the house, softens hard rain, and makes a yard livable in August. At the same time, a large tree is a large, living water pump. It draws moisture through a root system that can spread well beyond its branches. If that system draws a lot of water from soil near one side of a house, and nothing puts moisture back, that soil can dry and shrink while other sides hold steady. That difference, as you now know, is what moves a foundation.

How roots seek moisture

Roots do not hunt for a foundation, and they do not crack sound concrete by force in the way many people imagine. Roots follow opportunity. They grow where soil is looser, where moisture is available, and where oxygen is present. They grow toward water only in the practical sense that roots

in moist soil thrive and keep extending, while roots in dry, hard soil slow down. Over years, a root system maps itself to where the water is.

That water map is uneven. Soil under the middle of a slab stays moist because it is covered. Soil at the perimeter cycles wet and dry. Drip lines, watered beds, and low spots create pockets of moisture, and roots will use any of them. A plumbing leak near the house can keep one area damp for a long time, and roots may grow toward that steady supply. The leak itself is the bigger problem and should be repaired, but it explains why roots are sometimes found where they surprise a homeowner.

Distance and size: thinking in proportions

There is no magic distance that makes every tree safe or every tree dangerous. What matters is proportion: how large the tree will be at maturity, how close it is, what kind of soil you have, and how the moisture around the house is managed.

A useful way to think about it is the mature size of the tree, not the size it was when it was planted. A small ornamental tree that tops out modestly, planted a reasonable distance from the house, places a very different demand on soil moisture than a large shade tree that will grow tall and wide with a canopy spreading over the roof. Big trees need big volumes of soil water. If most of that volume lies right beside a foundation, the tree and the house will be sharing — and competing for — the same moisture.

As a general guide, the larger a tree will become, the farther from the foundation it should be planted. Think in terms of mature height and canopy spread: a tree that will be large belongs well out in the yard, not in a narrow strip beside the house. When planting, ask a reputable local nursery about mature size for our climate, and give the tree room to be the size it wants to be. That decision prevents most conflicts before they start.

For trees already in place, judge them as they are and as they will be in ten years. A young tree fifteen feet from the house may be no concern today and a real consideration as it matures. A mature tree the same distance away, in clay soil, on the sunny side of the house, deserves closer watching during drought — soil checks on that side, attention to gaps at the slab edge, and steady moisture care where it is appropriate.

Root barriers, in plain terms

A root barrier is a physical barrier placed in the ground

between a tree and a structure, intended to discourage roots from growing into the soil right next to that structure. Barriers are commonly made of a durable material installed in a trench, deep enough to cover the zone where most roots would otherwise travel toward the house, and long enough to cover the side at risk — not just a short section directly in front of the trunk.

In plain terms, a barrier does not stop a tree from needing water, and it does not waterproof the soil. It redirects root growth downward or away at that line, so fewer roots occupy the soil immediately beside the foundation. The tree will still draw moisture from the rest of its root zone. That is why a barrier works best as part of a moisture plan, not instead of one. Even moisture care on the house side still matters after a barrier is installed.

Installing a barrier involves digging near a tree, and digging can cut roots. Cutting major roots can affect a tree's health and stability, especially if too much is cut or if the work is done carelessly. Depth, placement, and how much root is disturbed are not guesswork. Costs for barrier work vary widely with length, depth, access, and soil, so get local estimates rather than relying on a general figure. This is one of the jobs where an arborist's advice before anyone digs is especially valuable — more on that below.

A barrier is also not a cure for movement that has already happened, and it does not repair a foundation. If a home already needs repair, that repair, in our work, means pressed concrete piles, with cost varying widely by the home and the scope. A barrier may be part of protecting the result afterward, by reducing one source of drying on that side, but it should be sold to you — and understood by you — as prevention, not as a repair.

Shrubs and plantings at the foundation

Trees get most of the attention, but the shrubs planted tight against the house deserve a look too. A single small shrub is a small drinker. A full row of large, mature shrubs along a wall, all rooted in the narrow bed right at the slab, is a steady demand on exactly the soil you are trying to keep even.

Composite example: One side of a house has a dense row of overgrown shrubs in a narrow, unmulched bed, with no soaker hose and a wide eave keeping rain off. Every summer that side shows a dry gap at the slab while the rest of the house does not. The shrubs did not act alone — the eave, missing mulch, and missing water all contributed — but their thirst in that narrow strip was part of the pattern. Pruning them to size, mulching, and adding that side to the regular soaking routine addressed the whole pattern.

When a tree is too close

So when is a tree too close? No single measurement answers it for every house, but signs together raise the concern: a large-at-maturity tree whose canopy covers much of the house and whose root zone must lie largely beside the foundation; soil on that side repeatedly drying and pulling away despite reasonable watering; movement concentrated on that side; and roots visible at the surface running toward the house. Any one sign is only a clue. Several together are a reason to get professional eyes on it.

What acting on it means varies. Sometimes the right step is better moisture care and monitoring. Sometimes it is barrier work, pruning, or a change in how that side is watered. Sometimes, for a tree that is unhealthy, poorly placed, and a continuing problem, removal becomes a reasonable choice. That decision should be made with full information, because it cannot be unmade, and because removal itself changes the soil.

Why removal does not solve everything

While a tree lives, it keeps soil in its root zone drier than it would otherwise be. When it is removed, that drying stops. Over months and seasons, moisture returns to soil kept dry for years, and shrunk clay can swell again — unevenly and slowly, much like the sudden-soaking problem in Chapter 4. A foundation can move as that happens, sometimes upward on that side. Homeowners who expect doors to swing perfectly the next month are often disappointed, not because the decision was wrong, but because the soil needs time to reach a new balance.

Getting an arborist opinion — and using it well

An arborist is a tree professional. A qualified arborist can assess a tree's health, structure, and likely mature size, whether pruning would help or harm, how barrier digging would affect it, and whether disease, decay, leaning, or storm damage makes it a safety concern apart from the foundation. That is information a foundation contractor does not have in the same depth, just as an arborist will not diagnose your foundation. For structural questions about the house itself, consult a structural engineer. Each opinion makes the others more useful.

When you call an arborist, share what you have observed: which side dries out, where any movement shows, how long the tree has been there, and any plans you are considering, such as a barrier or a repair. Ask what they would do if it were their house, what they would watch, and what they

would not do. If removal is recommended, ask what soil and foundation changes to expect afterward, so you can plan monitoring rather than be surprised by it.

Trees are one of the best things about a Texas yard, and with 50 years of hands-on field experience, I have seen far more homes where trees and foundations lived together well than homes where a tree truly had to go. The difference was rarely luck. It was proportion at planting, steady moisture care, and early attention when one side started behaving differently from the rest. Respect the thirst around your house, manage it evenly, and most trees will give you shade for decades while your foundation holds its ground.

Chapter 7: Plumbing Leaks Under the Slab: The Hidden Foundation Killer

If soil moisture is the slow, steady force that moves Texas foundations, a plumbing leak under the slab is the quiet force that can undo everything while you are not looking. Add too much water in one place, for too long, and that spot behaves differently from the rest of the ground under your house. One corner stays swollen and soft while the other side dries and shrinks. The slab was built to be supported evenly. When that support goes away, the slab has to bridge and bend. That is when cracks widen, doors rack out of square, and a repair plan stops making sense until the leak is found and fixed.

Homeowners often picture a leak as a dramatic burst pipe. Under a slab, it is rarely dramatic at first. It is usually a slow drip, a pinhole, a tired joint, or a cracked drain line that releases a little water every day. Because the pipe is buried under concrete and soil, you do not see the water itself. You see the effects, sometimes months after the leak began. Learning to recognize a hidden leak early can save you from paying to lift a house that is still sitting over an active plumbing problem.

There are two broad families of plumbing under most slab homes, and it helps to know the difference. The first is the fresh-water system, sometimes called the pressure side. This is the water coming into your house from the city meter or well, running through supply lines to your faucets, toilets, water heater, washing machine, and outdoor spigots. Those lines are under pressure whenever the system is on. That means a fresh-water leak does not need you to run a faucet to keep leaking. It can leak around the clock, day and night, whether anyone is home or not. Even a small pressure leak can put a surprising amount of water into the soil over weeks because it never truly rests.

The second family is the sewer and drain system. These lines carry water away from sinks, tubs, showers, toilets, and appliances. They are not under the same constant pressure. They move water when you use a fixture, and then they mostly rest. A cracked or separated sewer line under the slab tends to leak in pulses, when water is flowing through it. That does not make it harmless. Repeated pulses in the same broken spot can wash fine soil away from around the pipe, create a void, and leave a section of slab with less support than it should have. Sewer leaks can also bring moisture and odors up through cracks, and they can keep a patch of soil wet in a way that looks a lot like a drainage problem from the surface.

Fresh-water and sewer leaks call for different tests and repairs, so a good diagnosis names which system is involved before anyone talks about digging. A high water bill points toward the pressure side. A problem that worsens after heavy laundry days or long showers may point toward the drain side. Symptoms overlap, and a house can have both at once. The goal here is to understand the language, recognize the signs, and know why testing matters before foundation work begins.

The signs of an under-slab leak are often subtle, so it helps to read them together instead of waiting for one perfect clue. One classic sign is a warm spot on the floor. If a hot water supply line is leaking under tile, wood, or vinyl, the escaping water can warm the slab and the flooring above it. Homeowners sometimes notice it with bare feet in the morning, a place in the kitchen or hallway that feels warmer than the floor around it for no clear reason. Not every warm spot is a leak, sunlight and appliances can warm a floor too, but a persistent warm patch in the same place, day after day, deserves attention.

Another sign is sound. In a quiet house, late at night, some homeowners hear a faint hiss or a steady running sound inside a wall or under the floor. If you can hear water moving when every faucet is off, every toilet has finished filling, and no appliance is running, write down when you hear it and where it seems loudest. That simple observation can shorten a plumber's search considerably.

Your water bill is another witness. A pressure leak that runs all day will show up as higher use even when your habits have not changed. Compare this month to the same month last year, and look for a steady climb that weather and guests do not explain. You can also note the meter reading, avoid using water for a set period, and check whether the reading moved. If it moved while the house used nothing, water went somewhere. That check does not locate the leak, but it tells you a leak is likely real.

Unexplained wet soil is another clue. If one flower bed stays soggy days after the rest of the yard has dried, if grass stays unusually green in one narrow strip along the foundation during a dry spell, or if soil against one side of the house never firms up, pay attention. A leak under the edge of a slab can travel outward and show itself at the perimeter first. The wet spot may not sit exactly over the break, but it tells you which side to investigate first.

Changes inside the house matter too. Doors shifting on one side of the home is a common pattern. When a leak swells or softens soil under one area, that area can heave up or lose firm support while the rest of the house stays put. A bedroom door that suddenly rubs at the top corner, a bathroom door that will not latch anymore, or new cracks that appear mainly on one end of the house can all be the house reporting uneven support underneath. One sticking door by itself might just be humidity in the wood. A cluster of changes on the same side, arriving together with a higher bill or a wet patch outside, is a pattern worth taking seriously.

Hypothetical example: Imagine a homeowner in Fort Worth who notices the guest bathroom door sticking in March. In April the water bill is higher than expected, and by May a section of hall floor feels faintly warm every morning. None of those clues alone felt urgent, so nothing was done. By late summer, cracks had opened above two doorways on that side of the house. A leak test later found a hot water line leaking under that end of the slab. The lesson is that clues gain meaning when they arrive together, in the same part of the house.

When a leak is suspected, professionals use a few plain ideas to confirm it. Leak detection is the process of narrowing down where water is escaping. For pressure lines, that can involve listening equipment that helps a technician hear water escaping under the slab, along with pressure checks. For drain lines, a camera sent through the line can show cracks, separations, and places where the pipe has shifted. Done well, it is a step-by-step narrowing, from which system, to which line, to which section.

Static testing is simpler than it sounds. For a sewer system, it generally means filling the drain system with water up to a set level and watching whether that level holds. If the level drops when nothing is being used, water is escaping somewhere it should not. Think of filling a bathtub and marking the water line, then coming back to see if it fell without anyone pulling the plug. A drop does not draw a map by itself, but it answers the first question: is this system tight, or is it leaking? Further testing then isolates which section is failing, so repair can stay focused.

Why does all of this have to come before foundation repair, or at least be planned together with it? Because lifting and supporting a house over an active leak is building on a moving target. If wet soil has swollen and lifted one area, lifting that area further can overcorrect it. If a sewer leak has washed out soil and left a void, supporting the slab without addressing the void and the broken line leaves the cause in place. And after a repair, a continuing leak will keep changing the soil moisture under the newly supported house, inviting the same uneven movement to return. Good foundation work starts with stable conditions underneath. Fixing the leak first, or coordinating the plumbing repair closely with the foundation plan, gives the repair a fair chance to hold.

Working with a licensed plumber is the right call here, and in Texas this work belongs in licensed hands. Bring your notes: when the bill changed, where the warm spot is, which doors shifted, and where the soil stays wet. Ask what test is being proposed and what question it answers. Ask whether both the pressure and drain systems were considered, since testing only one can miss trouble in the other. Ask for results in writing, and ask the plumber and foundation crew to coordinate access and timing so their plans do not conflict. Costs for detection and repair vary widely depending on the system, the location of the break, and how it is accessed, so treat any early number as a ballpark until the line is actually located and seen. A careful plumber who tests before digging will almost always save you money compared with opening the slab on a hunch.

If a test comes back clean, that is good news, not wasted money. It removes a major suspect and lets you focus on soil moisture, drainage, and trees. If it finds a leak, you have found a true cause, and fixing true causes is how houses stay fixed. In the next chapter we will look at rain and drainage, and how to move storm water away without drying the soil out.

Chapter 8: Drainage That Protects Without Drying You Out

Every Texas homeowner with a slab has heard the same advice, usually right after a foundation problem: keep water away from the house. The advice is sound, as far as it goes. Rain that pools against the foundation, roof water that dumps off the edge and pounds the same narrow trench week after week, and a yard that slopes toward the house instead of away from it will all load one side of the slab with far more moisture than the other side receives. Uneven moisture is the enemy. But there is a second half to the truth that gets left out too often. In our clay soils, stripping moisture away too aggressively can cause trouble of its own. Soil that is kept

bone dry right against the house while the soil a few feet out stays wetter will shrink, pull back, and leave the edge of the slab with less contact and less support. Good drainage is a balance, not a war on water.

Think of the goal this way: you want rain to leave in an orderly fashion, and you want the soil around your foundation to stay as evenly moist as you reasonably can, season after season. You are not trying to build a moat, and you are not trying to bake the ground dry. You are trying to avoid extremes. No standing water against the house after a storm. No single downspout flooding one corner while the rest of the perimeter stays parched. When homeowners understand that balance, the pieces, gutters, extensions, slope, and drains, make sense as parts of one system.

Start with the roof, because that is where the largest volume of water arrives. A modest Texas thunderstorm can drop a remarkable amount of water on a roof in a short time, and all of that water has to go somewhere. Without gutters, it sheets off the edge and lands in a line right beside the foundation, exactly where you least want a repeated soaking. Gutters collect that roof water and deliver it to a few chosen points, the downspouts, where you can manage it. That alone is a major improvement, but only if the gutters are sized sensibly for the roof, kept clear of leaves and grit, and actually attached and sloped so water flows toward the downspouts instead of spilling over the back or sitting in a sagging run.

Downspouts are where many good gutter systems fail in practice. A downspout that ends right at the base of the wall has simply moved the problem from a long line to one concentrated point. Extensions matter. In general terms, downspout extensions or buried discharge lines should carry roof water well away from the foundation and let it out where the ground can receive it without sending it back toward the house or onto a neighbor in an unfair way. Check where each downspout actually discharges. Walk the house after the next rain and look. If the extension has been crushed by a mower, disconnected at the elbow, or aimed at a bed that funnels water right back to the wall, you have found a cheap fix that matters more than many expensive ones.

Surface slope is the next piece, and it is the quiet workhorse of drainage. In general terms, the soil and paving right next to the house should fall gently away from the foundation so rain that lands near the wall keeps moving outward instead of ponding. Over the years, beds get topped up, mulch builds high against the brick, soil settles, and walkways tilt. A slope that was fine when the house was built can quietly reverse in one section. You do not need instruments to spot the worst of it. After a rain, look for puddles that hug the house and linger. Look for water stains, algae, and soil lines on the brick that

show where water has been sitting. Those marks are a record of what the water has been doing when you were not watching.

At the same time, be careful about solving slope problems by piling soil high against the house. Raising beds above the top of the slab or burying weep holes in brickwork creates new problems, including hiding termite activity and trapping moisture against the wall itself. The aim is a gentle fall away from the house with the foundation still properly exposed, not a berm stacked against the brick. If a section truly needs regrading, it is often modest work, but it should respect those limits. When paving is involved, a driveway or patio that has settled and now drains toward the house deserves attention too, because concrete is very good at collecting water and delivering all of it to one low corner by the wall.

French drains deserve an honest explanation, because they are sold as a cure for almost everything and they are not. A French drain, in plain terms, is a trench filled with gravel or rock, often with a perforated pipe in it, designed to collect water that is moving through the soil and carry it to a discharge point. It can be genuinely useful in the right situation: a side yard that collects subsurface water, a low area that stays saturated because water is seeping through the ground toward the house, or a place where surface solutions alone cannot intercept water that is traveling underground. Installed with a proper outlet that drains by gravity to a lower point, it gives that collected water somewhere to go.

Here is what a French drain cannot do. It cannot fix a plumbing leak. It cannot lift or support a foundation. It cannot help much if it has no lower place to discharge to, because water in a pipe still needs to run downhill to get out. It cannot stop clay soil from shrinking during a drought, and it is not a substitute for gutters moving roof water away in the first place. It can also clog over time with silt and roots if it is built without care or never maintained. Perhaps most important for this chapter, a drain placed tight against a foundation and run aggressively can over-dry the soil on that side in dry weather if it keeps intercepting and removing moisture the soil would otherwise hold. That is the balance problem again. A drain is a tool for a defined water path, not a default answer for every wet yard. Costs vary widely with length, depth, soil, and what the trench has to pass through, so get the purpose stated plainly before you agree to one: what water is it collecting, and where exactly will that water come out?

Composite example: Picture a house in Arlington where the back corner of the slab kept showing movement while the front stayed stable. The roof had good gutters, but one back downspout discharged into a flower bed enclosed by edging

that acted like a small dam. Every storm filled that bed like a tub, and the water soaked in right beside the back corner for days. A French drain was proposed first. A simpler look showed the real fix was different: extend that downspout past the bed, open the edging so the bed could drain outward, and adjust the bed soil so it fell away from the wall. The corner stopped getting its repeated soaking, and no drain was needed. The honest lesson is to follow the water before buying a system to move it.

Do not forget the water that does not start on your lot. Neighbor drainage and street drainage shape what your soil experiences, especially on smaller lots and sloping streets. A neighbor who regrades, adds a pool, or extends several downspouts toward your shared line can change how much water arrives at your side yard after every storm. Most of the time this is not malice, it is a project done without thinking about the next lot downhill. A friendly conversation, held early and supported by what you have seen after rains, solves more of these cases than any argument held later. On the street side, watch how the curb, gutter, and storm drains handle a heavy rain. If the street floods and water backs up into your front yard, or if a blocked storm drain sends a sheet of water across your lot, that is worth reporting to the city and worth noting in your own records, because repeated street flooding can explain movement at the front of a house that otherwise has good drainage.

Checking after a hard rain is the habit that ties this chapter together, and it costs nothing. When a storm has passed and it is safe, walk the perimeter slowly and take photos. Where is water standing, and how close is it to the wall? Which downspouts overflowed or disconnected? Does any bed hold water like a bowl? Does water from the street or a neighbor enter the lot, and where does it go? Take the same photos after the next few storms. A pattern across three rains is far more useful than an opinion after one, and dated photos help any professional give grounded advice instead of a guess.

Balance takes patience during drought as well. The same homeowner who carefully moves storm water away in April may need to think about even, moderate moisture care in August, which the earlier chapters on soaker use cover in detail. Drainage and moisture care are not opposites. Drainage handles the excess, the sudden storm load that would otherwise pond and soak one side. Moisture care handles the deficit, the long dry stretch when clay pulls back from the slab. Houses do best when both jobs are done moderately and consistently, rather than either one being done to an extreme. If you remember one sentence from this chapter, make it this one: move the flood away, keep the soil even, and check what the water actually did after it rained. In the next chapter, we will go inside the repair itself and

explain, in plain language, how pressed concrete piles support a house and what it means when a pile reaches refusal.

Chapter 9: Inside the Repair: Pressed Concrete Piles to Refusal, Explained Simply

When a foundation has moved enough that moisture care and drainage corrections alone will not restore support, homeowners are often advised to have piles installed. That conversation can feel intimidating. Heavy equipment appears in the yard, holes are dug along the house, and words like refusal get used as if everyone already knows what they mean. This chapter slows that conversation down. It explains, in plain language, what a pressed concrete pile is, how it is installed using the weight of your own house, what refusal actually proves, and what a lift can and cannot promise. This is an explanation, not a sales pitch. A homeowner who understands the method can ask better questions, read a repair plan with clear eyes, and take care of the house properly after the work is done.

A pressed concrete pile is a column built underground, one short segment at a time, directly beneath the edge of your foundation. Each segment is a solid, precast concrete cylinder, roughly the shape of a large can, with a smooth hole through its center in many systems so segments can be guided and aligned as they stack. The segments are not exotic. Their strength comes from good concrete, from being stacked straight, and above all from where the finished pile ends up: standing on or in ground firm enough to carry the load placed on it. Think of the pile as a leg lowered through weak or shifting upper soil until its foot finds ground that can be trusted. The house load travels down the slab edge, into the top of the pile, down through the stack of segments, and into that firmer ground below.

Installation begins with a modest excavation at each pile location along the foundation, giving the crew room to work under the edge beam of the slab. A bracket or a direct bearing arrangement connects the work to the foundation, depending on the system and the location, and a hydraulic press is set over the spot where the pile will go. Then the pressing begins. The first concrete segment is placed and pressed downward into the soil. When most of that segment has been driven down, the next segment is set on top of it, aligned, and pressing continues. Segment follows segment, one at a time, each new piece pushing the stack deeper. The pile is quite literally built as it descends, which is why you will see stacks of identical concrete segments staged near each hole on the day of the work.

The force that drives the pile comes from the house itself. The press works against the weight of the structure above it, using that weight as resistance while it pushes the segments down. This is an elegant idea, and it is also a built-in test, which we will come to shortly. As the pile goes deeper, it passes through the upper soils, the very clays that swell when wet and shrink when dry and that caused the trouble in the first place. The goal is to get below the zone where moisture swings do the most moving, down to soil or material that stays far more consistent through wet seasons and droughts. Depth is not chosen by a fixed number on a chart. One side of a Texas house may reach firm ground at a shallower depth than the other side, because the ground itself is not uniform. Each pile finds its own depth.

That brings us to the most important word in this chapter: refusal. A pile is said to reach refusal when it stops advancing under the pressing force, or advances so little that continuing would risk lifting or damaging the structure instead of driving the pile deeper. In plain terms, the ground below the pile is pushing back as hard as the house is pushing down. Refusal is not a guess about the soil and it is not a promise read off a soil map. It is a physical demonstration, at that exact spot, on that exact day, that the ground under the foot of the pile can resist a load comparable to the load the house will place on it. The pile stopped because the earth proved it could hold.

Why is refusal the test that matters? Because it answers the only question a pile really has to answer: will this ground carry this house, here? Soil reports, neighborhood experience, and depth records from nearby jobs are all useful background, and experienced crews use them to plan. But none of them can substitute for the moment the pile itself meets the ground it will stand on. A pile stopped early, before refusal, may be standing in soil that will keep compressing or shifting with the seasons, and a support that keeps moving is not much of a support. A pile pressed to refusal has passed a load test built into its own installation. That is also why a responsible crew records the depth and behavior of each pile. Two piles a short distance apart reaching refusal at different depths is normal and honest. Identical depths all the way around a house would be the surprising result.

Hypothetical example: Consider a home in Grand Prairie where piles are being installed along the back wall. The first pile reaches refusal after a moderate stack of segments. The next pile, only a short distance away, keeps going noticeably deeper before it refuses, because the soil there contains a softer pocket the first pile never touched. A third pile refuses at a depth between the two. Nothing has gone wrong. The crew has simply learned, pile by pile, what the ground under that wall is actually like, and each support now stands on ground that proved itself. That variation is the method

working as intended, not a flaw in the plan.

Piles are placed in two general settings, exterior and interior, and it helps to know the difference. Exterior piles are installed along the outside perimeter of the slab, where the crew can dig alongside the foundation and work in the open. Most homes need support mainly at the perimeter, because the edge of the slab is where soil moisture changes are greatest and where movement usually shows first. Interior piles support points inside the footprint of the house, under interior load-bearing areas that have also lost support. Reaching those points requires more invasive access, which can involve tunneling beneath the house from outside or opening a section of floor inside, depending on the home and the plan. Interior work is therefore planned carefully and only where the pattern of movement shows it is truly needed. A good repair plan will show you, on a simple drawing, where each pile is proposed and why that location was chosen.

After the piles are in and have reached refusal, the conversation turns to lift. Lifting means using the installed piles as firm points to raise a settled section of the foundation back toward its original position, in a controlled way, a little at a time. Homeowners should hear both halves of the truth about lift. A careful lift can close cracks, bring floors closer to level, return doors and windows to working order, and most importantly put the house back on solid, proven support so further settlement in those areas is arrested. For many homes, stopping the movement and recovering a good part of the position is a genuine and lasting improvement.

What lift does not promise is perfection. A house that has moved for years has often bent, cracked, and adjusted in ways that do not fully reverse without risking new damage. Raising one area too aggressively can crack tile, stress plumbing, or open new cracks elsewhere, which is why experienced crews lift conservatively and watch the house as they go. Some cosmetic cracks will remain and need patching after the structure settles into its supported position. A floor may end up much improved without measuring perfectly level in every spot, because the goal is a stable, supported house, not a risky contest to chase an instrument reading. Anyone who guarantees a house will be made perfectly level, or that every crack will disappear and stay gone regardless of how the soil moisture is cared for afterward, is promising more than this work can honestly deliver. Costs for pile work vary widely with the number of piles, their depth, interior access, and site conditions, so a written plan with pile locations and terms matters far more than a quick verbal ballpark.

The last truth of this chapter is the one that returns us to the beginning of this book: piles do not end your responsibility for moisture. A pile supports the house at firm ground below the

active clay, and that is a major protection. But the soil near the surface still swells and shrinks, floors and finishes still respond to how evenly the ground around the house is kept, and plumbing leaks and poor drainage can still cause trouble that no pile was designed to prevent. Homeowners who keep up the balanced habits from the earlier chapters, orderly drainage away from the house, even moisture during drought, prompt attention to leaks, and a walk around the perimeter after hard rains, give their repaired foundation the conditions it needs to stay quiet for the long term. The piles hold the ground. Your habits protect the piles' work. Together, that is how a Texas house stays where it belongs.

Chapter 10: After the Repair: The First Year and Every Year After

The day the crew finishes can feel like the end of a long story. The house has been lifted, the pressed concrete piles are in the ground doing their quiet work, and the worst of the worry is behind you. In another sense, that day is the start of a new chapter: the first year of living with a repaired foundation, and learning how your house settles into its new, supported position.

Homeowners who know what to expect in that first year do far better than homeowners who expect perfection on day one. Walls, floors, doors, and plumbing lines spent years adapting to a sagging foundation. When the foundation comes back up, everything attached to it must adapt again. That adaptation is normal — not a sign the repair failed.

The First Few Weeks: Small Sounds and Small Shifts

In the first days and weeks after a lift, you may hear small pops and creaks, especially in the evening when temperatures drop. Wood framing that twisted slowly over many years does not always move back in one smooth motion. It adjusts in little steps. A trim board may separate slightly. A nail pop may appear in drywall. These small signs are common and, in most cases, purely cosmetic.

Keep your expectations steady. The goal of a lift is support, stabilization, and a return toward level as conditions safely allow — not a promise that a thirty-year-old house will measure like a brand-new one. A good crew will tell you where they stopped lifting to protect plumbing, framing, or finishes. That honesty matters more than a perfect number.

Drywall Cracks: Why They Appear After

Good Work

One of the most common calls after a repair is about drywall cracks. "We fixed the foundation — why is there a new crack above the bedroom door?" The answer is simple: drywall is stiff and brittle, while a house frame flexes. When the foundation sank, drywall cracked or compressed and hid stress. When the foundation rises, the stress changes direction. Old cracks may close tight. New hairline cracks may open, often at door and window corners, ceiling joints, and where walls meet.

These post-lift cracks usually appear in the first weeks to months, and by themselves they do not mean the foundation is moving again. They mean the finishes are adjusting. A hairline crack that appears and then stays the same is a cosmetic matter. A crack that keeps widening month after month, a door that gets steadily worse, or a large crack that reopens after proper repair deserves a call and a fresh look. Keep notes and dated photos: a steady record turns worry into information.

Doors and Windows: Adjustments Are Part of the Job

Doors tell the truth about a house, and after a lift they often need attention. A door that stuck badly may swing free afterward. A door that worked fine may rub lightly at the top corner. Both outcomes are normal. The frame around a door is a rectangle set into a wall, and when the wall moves even slightly, that rectangle changes shape.

Plan on a round of adjustments in the first few months. Sometimes the fix is simple: tightening hinge screws, planing a small high spot, or adjusting a strike plate so the latch catches. Sometimes a door needs to be re-hung by a carpenter. Wait until the house has had time to settle into its supported position before paying for fine carpentry — unless a door will not close or lock at all. Security and weather sealing come first; fine fitting comes after. Windows deserve the same patience. Most will work better after support is restored, and any that bind should at least be checked so they still lock.

Plumbing: Test Again, and Think Clearly About What It Means

If there is one post-repair step homeowners are tempted to skip, it is the plumbing re-test — and it is one of the most important. Many Texas houses have older drain lines under the slab, and those lines moved with the house. A lift can stress a line that was already thin, cracked, or bellied. A leak under a repaired foundation can wash out soil and create a

void, so you want to know the condition of your lines after the movement, not just before it.

A proper re-test generally means a licensed plumber checks the water supply system for pressure loss and tests the drains to see whether they hold water as they should. If the pre-repair test found a leak and you repaired it, the re-test confirms the fix. If the first test was clean and the re-test finds a new break, you have caught it early, while it is a plumbing repair and not yet a new foundation problem.

Keep the written results of every test with your foundation paperwork. A clean re-test after the lift is a valuable document if you ever sell. A repaired-and-retested line is nearly as good, because it shows the problem was found and finished, not hidden. If a plumber recommends work you cannot do right away, ask how urgent it is, and put the plan in writing.

Backfill and Soil Settling Around the Piles

During installation, soil is opened around the foundation so crews can place the piles and brackets. When the work is done, that soil goes back in. Freshly replaced soil is looser than soil that sat undisturbed for decades, and it will settle. Over the first months, especially after the first good rains, you may see low spots along the beam where the work was done. This is expected.

Settling backfill is not the same as your foundation settling. The piles are deep and supported; the loose surface soil is simply compacting. Your job is to add soil back as needed so the grade slopes gently away from the foundation, never toward it. Use clean fill soil, tamp it lightly, and re-check after rain. Keep soil below brick weep holes and the top of the slab edge, and correct any small channel that funnels roof water against the house.

Re-Establishing Even Moisture: The Main Job Now

Once the structure is supported, your central job for as long as you own the home is the one this whole book is built around: keep soil moisture around your foundation as even as you reasonably can, in every season. The piles carry the load to more stable soil, but surface soil still swells and shrinks. Even moisture will not make Texas clay stop moving entirely. It will greatly reduce the swings — and smaller swings mean fewer cracks, fewer sticking doors, and a longer, quieter life for your repair.

Start your watering routine as soon as your repair company says it is appropriate. In dry weather, that usually means

soaker hoses or a foundation watering system on a steady schedule, placed a short distance out from the foundation so water soaks down along the beam without ponding against it. In wet weather, the discipline reverses: no extra watering, gutters and drains working, no standing water next to the house. The goal is never "wet" and never "bone dry." It is "about the same, most of the time."

Hypothetical example: a homeowner in Fort Worth finishes a repair in late spring, waters faithfully through a dry July, then travels for three weeks in August with the system off. The sunny south side shrinks hard while the shaded north side stays closer to normal. By September a door is rubbing again — not because the piles failed, but because the soil made a big, uneven swing. A timer or a neighbor checking the system would have prevented it. Steady beats heroic. Build a routine you can keep even when life gets busy.

Patience With Cosmetic Repairs

Here is advice that will save you money: do not rush to patch, paint, and finish every cosmetic flaw in the first weeks after a lift. Give the house time. Many experienced homeowners wait several months, and some wait through a change of seasons, before doing final drywall work and paint in the areas that moved most. A crack patched too early often reopens just enough to show through new paint, which means paying twice for the same work.

Use the waiting time well. Mark cracks lightly in pencil with a date, and photograph doors that rub. When you do repair cracks, do it properly: remove loose material, fill and tape where needed, sand, prime, and paint. Tile and grout that cracked before the repair should likewise be evaluated after the house has settled, not in the first week.

Keeping Records and Elevation Paperwork

From now on, you are the keeper of your foundation's file, and that file is worth real money and real peace of mind. Keep in one folder: your repair contract, the pile location diagram, pre- and post-repair elevation readings, any warranty document, plumbing test results before and after, invoices and proof of payment, and your dated photos and crack log. Add your own note: the date of the lift, the movement reported, and any areas where the crew stopped lifting on purpose to protect the house.

Elevation paperwork confuses many homeowners, so think of it plainly. Elevations are floor-height measurements taken at many points, compared to a reference point. They show the shape of the floor — where it sat low, and where it sits after support. No single number tells the whole story; the pattern

tells the story. Keep the diagrams even if you do not fully understand them today. A future buyer or a structural engineer you hire someday will read them fluently.

Finally, schedule a follow-up. Many companies will re-check a home after a period of time, and even if yours does not offer it automatically, ask for a check at the one-year mark. That steady attention — not worry, just attention — turns a one-time repair into a house that holds its ground year after year. The hard work is done. Now the quiet work begins, and it is work you can absolutely do.

Chapter 11: Buying, Selling, and Living With a Repaired Foundation

At some point, almost every repaired foundation meets the real estate market. Maybe you repaired your home and now you are selling it. Maybe you are buying a home and the seller hands you a stack of foundation paperwork. Maybe you plan to stay thirty years, rent the house out, or pass it to family. In every case, the same truth holds: a repaired foundation with good paperwork and a clear story is not a secret to hide. It is a known, addressed condition — and in Texas, where clay soil moves under many homes, that is a stronger position than people first assume.

This chapter is general information, not legal advice. Rules and forms change, and every transaction is different. For anything that affects a sale, a contract, or your legal duties, check the current Texas requirements and talk with a qualified real estate professional or an attorney who handles Texas property. What follows will help you understand the questions, organize the paper, and have a smarter conversation with those professionals.

Selling a Home With a Repaired Foundation: Disclosure in Plain Terms

Texas sellers generally complete a Seller's Disclosure Notice that asks about the condition of the property, including foundations, past repairs, flooding, and other known facts. The guiding principle most professionals give is simple and wise: disclose what you know, honestly and completely, and answer the form as it is written. If the foundation was repaired, say so. If you have a warranty, say so. If there was a plumbing leak under the slab, say what was done about it. Minimizing or leaving a known repair off the paperwork creates the very trouble honest disclosure avoids — disputes later, when memories differ and money is on the line.

Do not speculate beyond what you know. You can state the date of the repair, the company that did it, and the method used — pressed concrete piles — and provide the documents. You do not need to promise a buyer the house will never move again, because no honest person can promise that about any Texas house. You also do not need to volunteer fears as if they were facts. "The foundation was repaired in this year, by this company, with this paperwork, and here is the elevation record" is a complete, truthful answer.

Gather your file before you list the home, not after a buyer asks. That file — contract, pile diagram, elevations before and after, warranty, plumbing tests, and invoices — should be ready to share. Sellers who produce organized paperwork early almost always have smoother transactions than sellers who say the papers are "somewhere." If you have lost documents, contact the repair company and ask for copies. Price and timing conversations belong with your real estate agent. In many Texas neighborhoods, a documented repair is treated as a normal part of a home's history. An undocumented repair, or signs of movement with no repair at all, is what tends to slow a sale down.

Transferable Warranties: Questions Worth Asking

Many foundation warranties can transfer to a new owner, and a transferable warranty is a genuine selling point. But warranties differ widely in what they cover, how long they last, and what a transfer requires, so read yours closely and ask direct questions while you still have time to get answers in writing.

Ask the company that issued the warranty: Is it transferable to a new owner, and if so, how many times? Is there a transfer fee, and how much is it? Fees vary widely, so get the current figure from the company rather than relying on memory. Is there a deadline after the sale by which the transfer must be completed? What exactly does the warranty cover — re-adjustment of the installed piles if that area settles, labor, materials, or only certain parts of the work? What does it exclude? Are there conditions the new owner must meet, such as maintaining drainage or a watering routine, for coverage to remain in place? What paperwork does the company need from seller and buyer to record the transfer?

Get the answers in writing and put them in the file. A buyer who can see the terms, transfer steps, and deadline in plain print will feel far more confidence than one who is simply told, "It has a lifetime warranty" — a phrase that means different things at different companies. The document is the promise. If you are the seller, start the transfer conversation

before closing, so the buyer is not racing a deadline during moving week. Who pays any fee is a normal point of negotiation, settled in the transaction paperwork.

Buying a Home With a Repaired Foundation: What to Ask For

If you are the buyer, a repaired foundation should start a set of questions, not end your interest. A house repaired and documented has dealt with its movement openly. Your job is to verify the story.

Ask for the complete paperwork set: the repair contract, the diagram showing pile locations and depths if available, pre- and post-repair elevation readings, the warranty and its transfer terms, plumbing test results from around the time of the repair, and any later follow-up elevation checks. Ask when the repair was done and who did it, then check that the company is still operating and honors its warranties. Ask whether any plumbing leaks were found under the slab and how they were fixed, because a house can have excellent piles and still be at risk from an old, leaking drain line.

Read the elevation drawings as a pattern. Look for how much movement existed before repair, how much was recovered, and whether later readings show stability over time. A home repaired eight years ago with steady readings since is telling a reassuring story: the repair held, and the owners maintained the home. A home repaired eight months ago has less track record — not a failure, but a reason your own monitoring in the first years matters more.

Walk the property with the eye you have built reading this book. Check grading and drainage. Look for standing-water paths, gutters that dump at the foundation, large trees close to the house, and signs of a watering routine — or the lack of one. Look inside for fresh, heavy cosmetic patching done right before listing, and ask what lies under it. None of this requires expertise. It requires observation, and asking for paper. If questions remain, you may choose to hire a structural engineer for an independent evaluation, or a foundation company for an inspection, during your option period — discuss timing and access with your real estate professional. An independent set of eyes is money well spent when it turns an unknown into a known.

Composite example: two similar homes sit on the same street. The first shows cracks, and the seller says the foundation "has never been a problem" but offers no records. The second was repaired six years ago and comes with a full file, a transferable warranty confirmed in writing, clean plumbing tests, and elevation checks showing a stable floor since the

work. Many experienced buyers calmly choose the second home — because known and documented beats unknown, every time.

Why a Documented Repair Can Be a Strength

It helps to say this plainly, because sellers often fear the opposite: in much of Texas, a repaired foundation is not a scarlet letter. Clay soil is a fact of life from the Red River to the Gulf Coast, and many homes will need support work at some point. A home whose movement was addressed with pressed concrete piles, whose plumbing was tested, whose warranty transfers, and whose owners kept up with drainage and watering is, in practical terms, ahead of a home that has never been repaired but is quietly beginning to move.

The strength is not the repair alone. It is the repair plus the proof plus the maintenance. That combination tells a buyer three things: the big structural question has been answered, the answer is documented by people who stand behind it, and the home has been cared for by owners who paid attention. Buyers hope to find exactly that in every system of a house — roof, electrical, plumbing — and the foundation is no different. Sellers, help your buyer see the story: leave the watering instructions, timer settings, and a short note about your seasonal routine with the house papers.

Renting and Long-Term Holding Notes

If you keep the home as a rental or hold it for family, your maintenance duties matter more, because they must survive a change of occupants. Tenants, however good, will not watch a foundation the way an owner will unless you make it easy and clear for them.

Put foundation care into the practical rhythm of the property. State in plain language, in whatever agreement your professionals advise, who is responsible for running the watering system, keeping gutters and drains clear, and reporting plumbing leaks promptly. Slow leaks and running toilets are foundation issues in a rental, not just plumbing annoyances, because water under or around a slab does damage quietly for months. Schedule your own walk-throughs at least twice a year: check grading, look for new cracks, run every faucet, look under sinks, and confirm the watering routine is actually happening.

For long-term owners who stay put, the message is the same, stretched over decades. Keep the file updated. Every plumbing repair, every elevation check, every major tree removal near the house — note the date and keep the invoice. If you ever need warranty service, that record makes the

conversation short and factual. And every few years, take a fresh, honest walk around your home with the eyes this book has given you. A house that is watched does not surprise its owner often. Whether you are buying, selling, renting, or staying, the principle does not change: paper, honesty, and steady care turn a repaired foundation from a question mark into a settled fact — good for the house, good for the people in it, and good for whoever owns it next.

Chapter 12: Your Year-Round Foundation Care Calendar

Everything in this book comes down to a rhythm. Foundations in Texas do not usually fail in one dramatic week. They react, slowly, to seasons that repeat every year: winter cold snaps, spring rains, summer drought, and the relief of fall. If your care follows those seasons — a little attention at the right time, every time — you will catch most problems while they are still small and far less costly.

Think of this calendar as a pattern to adapt, not a set of orders. A home in El Paso lives a different water year than a home in Houston, and a shaded lot with mature oaks asks different questions than a new lot in open sun. Use the seasons below as your framework, and adjust the details to your soil, trees, rainfall, and crack log.

Winter: Quiet Checks and Protection From Extremes

Winter in Texas can be mild for weeks and then deliver a hard freeze with little warning, and that swing is what makes winter a foundation season at all. Cold itself does not shrink clay the way drought does, but winter is when plumbing is most at risk — and water where it does not belong is one of the fastest ways to hurt a foundation. Before the first serious freeze, insulate exposed pipes, cover outside faucets, and know where your main water shutoff is and how to use it. If a pipe bursts, shutting the water off quickly is the difference between a plumbing bill and a plumbing bill plus soil washed out from under your home.

Winter is also your best indoor inspection season. You are inside more, and low, angled light shows cracks honestly. Walk the house with a flashlight held along the walls. Check door and window corners, run a hand along known cracks, and compare them with your log. Photograph anything that has changed. Check that every door still latches and every window still locks. Test faucets and look under every sink for slow drips that could run unnoticed for months.

Outside, on a mild day, do the winter exterior round. Confirm soil still slopes away from the house after fall rains and any settling. Check that downspouts discharge well away from the foundation and extensions have not been knocked loose. If you use a foundation watering system, winter is when you reduce it — most Texas homes need far less supplemental watering in cool months, and some need none in a wet winter. The soil should stay roughly consistent, not soggy. In a genuinely dry winter, light, occasional watering on the driest exposures may still be wise. Let your soil, not the calendar alone, make the final call.

Spring: Rain, Drainage, and the Big Review

Spring brings the rains, and rain tests every drainage decision you have made. Stand outside — safely, after the heaviest downpour has passed — and watch where the water actually goes. Does it sheet away from the house, or pond against the beam? Do gutters overflow at one corner and dump a waterfall where you least want it? Does the yard hold a shallow lake for a day after every storm? Water standing next to a foundation swells clay on that side, and uneven swelling lifts unevenly. Your spring job is to find those spots while the evidence is in front of you, and fix the grading, gutter, or drain that causes them.

Clean the gutters in spring, and check them again after heavy leaf and seed fall. A clogged gutter is not minor housekeeping on a slab home; it delivers hundreds of gallons of roof water to one spot of soil. Confirm downspout extensions and splash blocks are in place, and that buried drain lines still flow freely at their exit points.

Spring is also the season for the big review. Pull out your crack log, photos, and foundation file. Compare this spring's pictures with last fall's. Which cracks moved? Which doors changed? Is there a pattern — one side of the house, one plumbing line, one big tree? Patterns point to causes, and causes can be fixed. If your home is under warranty and something has genuinely changed, spring is a calm time to call and ask for a check, records in hand. Schedule plumbing concerns promptly: a slow leak found in April is a small repair; the same leak found in October has had a summer to wash out soil. If you garden, make planting decisions with the foundation in mind — keep thirsty plantings and new trees at a respectful distance, and avoid beds that hold water against the beam.

Summer: Drought Discipline and the Watering Routine

Summer is the main event in Texas foundation care. Weeks without rain, heat that bakes the ground, and sun that pulls

moisture from the soil will shrink clay hard — fastest where sun hits longest and where big trees pull water from underneath. The south and west sides of most homes take the hardest drying. This is the season your watering routine earns its keep.

Run soaker hoses or a foundation watering system on a steady, moderate schedule through dry stretches. The aim is even moisture — soil that stays about the same around the whole perimeter, not soil that swings from soaked on Sunday to cracked open by Friday. Short, frequent, consistent watering usually serves that goal better than rare, heavy soaking. Place lines a short distance out from the foundation so water soaks down along the beam. Check the system itself monthly in summer: timers fail, hoses kink, emitters clog, and a system you believe is running but is not is worse than no system, because it gives you confidence you have not earned.

Watch the soil with your own eyes. A small hairline separation where soil pulls slightly from the foundation can appear in the worst weeks; wide gaps are a signal to step up watering consistency and check for other causes, such as a large tree on that side. Keep mulch in beds — it slows evaporation. Summer is also irrigation season, and a broken sprinkler line or leaking hose bib can quietly flood one corner for weeks, so walk the yard while irrigation runs at least once a month and look for soggy spots or unusually green patches. Be thoughtful, too, with summer projects — pools, landscaping, fences, tree removals — because each changes how water moves and soil dries. Note the dates in your file, and watch those areas for a year afterward.

Fall: The Reset Season

Fall is the reset: the season to bring everything back to a known, good state before winter, and to learn what the year taught you. As temperatures ease and rains return, taper watering gradually rather than stopping it all at once after a dry summer. Sudden changes, in either direction, are what you are always trying to avoid. Let the soil return to a moderate, even state around the whole house.

Do a full fall inspection, inside and out, with log and camera in hand. Measure and photograph your reference cracks. Test every door and window. Clean the gutters again after leaf fall, checking downspouts and drainage exits once more. Top up settled soil anywhere the grade has dropped near the foundation, especially over backfilled areas from past work, so winter rains run away from the house instead of collecting against it.

Fall is the right time for the year's paperwork hour. File invoices, plumbing receipts, and any inspection or elevation

reports, and update your notes: what changed, what you fixed, what you are watching. This single hour keeps your file the kind described in Chapter 11 — the file that protects you whether you stay for decades or sell next spring. Fall is also a kind season for cosmetic work you patiently postponed after a repair, since conditions are often stable enough for patching and painting to hold. If you are planning larger work for next year, get proposals in this calm season; costs for such projects vary widely by home and region, so compare plans, not just numbers.

Hypothetical example: a homeowner near Abilene treats the first Saturday of October as a fixed appointment — gutters cleaned, grade checked, cracks photographed, file updated, watering tapered, coffee made first. The whole round takes about three hours, once a year. Over a decade, that habit has caught a leaking hose bib, a clogged drain exit, and one slow drain leak, each fixed small because each was found early. That is the philosophy of this book in one Saturday.

The Monthly Habit Summary

Seasons carry the big work, but months carry the habit. Whatever the season, a short monthly round keeps you connected to your house. It does not need to be long or perfect. It needs to be regular.

- Walk the outside of the house once a month. Look at grading, soil contact, downspouts, and any place water could collect against the foundation.
- Check your watering system monthly — more often in summer. Confirm timers, hoses, and lines are actually running as you intend.
- Look at your reference cracks and your most honest doors. Note any change in your log with a date and a photo.
- Glance under sinks and at visible plumbing. A slow drip found this month is a small fix; the same drip found next season may not be.
- After any major storm, do a quick drainage check. Where did the water go, and did anything change?
- Keep every receipt, report, and note in your foundation file as it happens, not in a pile to sort someday.
- Once a month, ask the simple question this book has trained you to ask: is the moisture around my house staying about even? If the honest answer is yes, your foundation is getting what it needs most.

That is the whole calendar: winter protection, spring drainage and review, summer watering discipline, fall reset, and a small monthly round to hold it together. Together, repeated year after year, they are how a Texas house on clay soil stays a steady, comfortable, valuable home.

Conclusion: Holding Ground for the Long Haul

You picked up this book because your house moved, or because you were afraid it might, or because you wanted to understand the ground under a Texas home before a small worry became a large one. However you arrived here, you are leaving with something more valuable than a list of repairs. You are leaving with a way of seeing your home — from the soil up — and a set of habits that will serve you for as long as you own it.

If you remember nothing else, remember the ideas that ran through every chapter. First, even moisture is the foundation of everything. Texas clay will move; that is its nature. But soil that stays roughly the same, season to season and side to side, moves far less, and a house on steadier soil lives a far quieter life. Your watering routine, your gutters, your grading, and your drainage all serve that single idea.

Second, read your house early and often. Cracks, doors, floors, and trim are a language, and you now speak it well enough to know the difference between a cosmetic whisper and a structural warning. A dated photograph and a line in a log will always beat a worried memory. Small changes found early stay small — and small problems are the kind a homeowner can solve calmly, on a normal budget, without turning life upside down for a season.

Third, fix leaks fast. Water under a slab or pooling against a beam is never a "someday" problem. A plumbing repair made promptly protects the soil, the foundation, and every repair dollar you have already spent. Of all the money a homeowner spends on a foundation, the money spent stopping water quickly is usually the best spent of all.

Fourth, hold the standard when work must be done. A real repair means real support: pressed concrete piles, installed with care, measured honestly, plumbing tested, and paperwork you can hold in your hand. Refuse shortcuts, vague promises, and diagnoses made from the curb. Your home deserves the full job, done once, by people who will put their name and their warranty in writing.

Fifth, keep the record. Your foundation file — elevations, pile diagram, warranty, plumbing tests, photos, and notes — is part of the house now, as real as its roof. It protects you while you live there, it strengthens your hand if you ever sell, and it is a gift to whoever owns the home after you. A house with a story that can be proven is a house people can trust.

Beyond those ideas stands the quiet truth this book has been

pointing toward: steady care beats panic, every time. The homeowners who fare best on Texas clay are not the ones who worry the most or spend the most. They are the ones who walk their house each month, keep their file, run their water in a drought, clear their gutters before the rains, and make one calm phone call when something changes. None of that requires talent. It requires only attention, repeated — and attention, repeated, is something you have already proven you can give, simply by finishing this book.

So here is your charge for the long haul. Keep the moisture even. Keep the log current. Keep the file complete. Keep the standard high. And then go live in your house — cook in it, gather in it, raise a family or welcome grandchildren in it — without the foundation taking up space in your thoughts every week. That peace is what all of this work was for. A house that is watched over, on ground that is held steady, will hold you in return for many years to come.

There will be years when nothing much happens, and that is the point. A quiet year — no new cracks worth noting, no doors misbehaving, no leaks, no surprises after storms — is not luck. It is the visible result of all the small, unglamorous care in the chapters before this one. Learn to enjoy those quiet years and to trust them, while still taking your monthly walk. Boredom, in foundation care, is success wearing work clothes.

Thank you for trusting these pages with something as important as your home. Now take that first walk around your house, log in hand, and begin. You know what to look for. You know what to do. You have got this — and your house is going to be just fine.

Resources & Next Steps

If this book raised a question about your own house, start with the simple steps: walk the outside walls, check where roof water lands, look for a dry gap at the slab edge in summer or standing water after rain, and start a short log of doors, cracks, and changes with dates. If signs keep progressing, get an on-site foundation evaluation with measurements, and fix any plumbing leak first. For an independent opinion on a specific house, hire a structural engineer.

Travis Nech has spent 50 years in brick, masonry, and foundation work across Texas. He owns and operates Champion Brick Repair, Metro Foundation Repair, LintelLOCK, MortarMagic, and WhiteStone Construction.

- **Champion Brick Repair** — brick & masonry repair, Dallas-Fort Worth — championbrickrepair.com — (817) 900-6324
 - **Metro Foundation Repair** — pressed concrete pile foundation repair — metrofoundationrepair.com — (817) 523-1540
 - **LintelLOCK** — the field-developed lintel replacement system — lintlerepair.com — (469) 730-0650
 - **MortarMagic** — mortar color matching & the Mortar Bucket — mortarmagic.netlify.app
 - **WhiteStone Construction** — stone, ranch & property work, Hamilton TX country — (254) 723-5040
-

About the Author

Travis Nech has spent 50 years in brick, masonry, and foundation work across Texas. He owns and operates Champion Brick Repair, Metro Foundation Repair, LintelLOCK, MortarMagic, and WhiteStone Construction.

- **Champion Brick Repair** — brick & masonry repair, Dallas-Fort Worth — championbrickrepair.com — (817) 900-6324
- **Metro Foundation Repair** — pressed concrete pile foundation repair — metrofoundationrepair.com — (817) 523-1540
- **LintelLOCK** — the field-developed lintel replacement system — lintlerepair.com — (469) 730-0650
- **MortarMagic** — mortar color matching & the Mortar Bucket — mortarmagic.netlify.app
- **WhiteStone Construction** — stone, ranch & property work, Hamilton TX country — (254) 723-5040

Travis writes the way he works: plain language, honest limits, and methods proven in the field over decades. His books exist so a homeowner can walk into any repair conversation already knowing what good work looks like — and what questions make a contractor show it.